



ANALIZOR CARBON / SULF

CS-580A

ELTRA's CS-580A is the ideal elemental analyzer for simultaneous determination of carbon and sulfur in organic samples. It features a resistance furnace with vertical ceramic tube and uses ceramic crucibles as sample carriers.

An automatic sample loader allows for analysis of large numbers of samples without operator intervention. The sample loader is available in two versions to accommodate 36 or 130 crucibles. For reliable analysis of acidified samples (TOC analysis), both versions are available in an acid-resistance configuration.

The temperature can be set in steps of 1 °C to a maximum of 1,550 °C. Thanks to sample weights of up to 500 mg and more even inhomogeneous materials can be reliably analyzed. The CS-580 A elemental analyzer can be equipped with up to four independent infrared cells for measuring carbon and sulfur concentrations, allowing for a great variety of applications.

BENEFITS CS-580A

- | Fast, simultaneous elemental analysis of C and S, TOC and TIC
- | Configurable for one-element (C or S) or multi-element (C & S) analysis
- | Wide concentration range from 0.005 – 100 %
- | High weights possible for elemental analysis of heterogeneous samples
- | Optional autoloader with 36 or 130 positions (acid-resistant version available)



ANALIZOR CARBON / SULF CS-580A

ANALIZA OPERAȚIUNILOR ȘI A PROCESELOR

Operation of the CS-580 A elemental analyzer is simple, fast and convenient. The samples are weighed and registered in the software as manual analysis or analysis via autoloader. Typical sample weights are between 50 and 500 mg. After starting the analysis, the sample is introduced into the furnace and the combustion gases CO₂ and SO₂ are measured in up to four infrared measuring cells. The results of the elemental analysis can be exported via LIMS, report or text file.



Logging the sample into the software and weighing



Placing sample in autoloader and analysis



Measurement results and export

ANALIZOR CARBON / SULF CS-580A

CONFIGURATIONS AND OPTIONS

The elemental analyzer CS-580 A can be configured to meet a wide range of customer requirements. C, S and C/S configurations are available with up to 2 infrared cells for each element to cover a wide working range. Robust measuring cells for the reliable determination of sulfur in very high concentrations are also available.

The ELTRA CS-580 A series is perfectly equipped for TOC analysis according to DIN EN 15936 with optional acid-resistant autosamplers, as well as the optional TIC module.

An optional autoloader with 130 crucible positions is available for elemental analyses with high sample throughput.



Analyzer with optional TIC module



Autoloader with 130 crucible positions



Autoloader with acid-resistant plastic crucible holders


ANALIZOR CARBON / SULF CS-580A

PROBE TIPICE

The CS-580 A elemental analyzer is perfectly suited for measuring carbon and sulfur concentrations in matrices such as cenuși, materiale de construcții, coal, cărbune bituminos, ghips, calcar, ulei, materiale de plantare, cauciuc, sand, sol, calamină, tutun, deșeuri, ...



coal



sol



tutun

ANALIZOR CARBON / SULF CS-580A

PRINCIPIU DE FUNCȚIONARE

In the CS-580A elemental analyzers the sample is burnt in an oxygen atmosphere at temperatures of up to 1,550 °C. The furnace temperature can be freely selected in steps of 1 °C. The combustion gasses (CO₂, H₂O, SO₂) coming from the furnace pass through a dust filter. After the water vapor is chemically absorbed, the dried CO₂ and SO₂ gas is detected in the additional infrared cells. Depending on the configuration, it is possible to combine up to four infrared cells with different sensitivities to measure carbon and sulfur concentrations.

ANALIZOR CARBON / SULF CS-580A

DATE TEHNICE

Elemente măsurate	carbon, sulf
Probe	organic
Aliniere cuptor	vertical
Purtător de probă	creuzete ceramice
Domeniul de aplicare	agricultură, biologie, chimie / mase plastice, cărbune / centrale electrice, materiale de construcții, medicină / produse farmaceutice, mediu / reciclare
Cuptor	cuptor de rezistență (tub ceramic), reglabil pana la 1550° C (trepte de 1° C)
Metoda de detecție	absorbție în infraroșu
Numărul de celule IR	1 - 4
Material celula IR	Aur
Durată tipică de analiză	60 - 120 s
Reactivi necesari	hidroxid de sodiu, perclorat de magneziu
Gaze necesare	oxigen pur 99,5% (2-4 bar / 30-60 psi) aer comprimat (4-6 bar / 60-90 psi)
Alimentare	230 V, 50/60 Hz, curent max. de încălzire 2000 W
Dimensiuni (W x H x D)	55 x 100 x 60 cm (analizor) 85 x 35 x 45 cm (Autoloader pentru 130 creuzete)
Greutate	~ 90 kg (analizor) ~ 15 kg (Autoloader pentru 130 creuzete)
Echipament necesar	PC, monitor, balanță (rezoluție 0,0001)
Accesorii necesare	Autoloader (pentru 36 sau 130 de creuzete)
Accesorii opționale	modul TIC, stabilizator de tensiune 5 KVA

www.eltra.com/cs580A







INFORMAȚII DESPRE COMANDĂ

ELTRA CS-580A

(Please order PC, monitor, balance, Autoloader and consumables (starter-kit, anhydron, sodium hydroxide) separately)

Measuring ranges at 500 mg sample weight

2)

88100-4015		CS-580A	1xC	0.05 – 100% C
88100-4017		CS-580A	2xC	0.005 – 12% C 12 – 100% C
88100-4018		CS-580A	2xS	0.005 – 2% S 2 – 20% S
88100-4019		CS-580A	1xC + 1xS	0.05 – 100% C 0.005 – 2% S
88100-4020		CS-580A	1xC + 2xS	0.05 – 100% C 0.005 – 2% S 2 – 20% S
88100-4021		CS-580A	2xC + 1xS	0.005 – 12% C 12 – 100% C 0.005 – 2% S
88100-4022		CS-580A	2xC + 2xS	0.005 – 12% C 12 – 100% C 0.005 – 2% S 2 – 20% S



Further measuring range combinations on request

REQUIRED ACCESSORIES

PC, MONITOR, BALANCE


71015-1000	Computer with Intel Core i5-8400 Processor, 256 GB SSD; 8 GB RAM; Windows 10 operating system; keyboard; mouse
88400-0584	Monitor, TFT (23.8")
88400-0645	Balance (resolution 0.0001 g)
14535	Autoloader for 36 crucibles
14535-1001	Autoloader for 36 crucibles, acid resistant
14533	Autoloader for 130 crucibles
14533-1001	Autoloader for 130 crucibles, acid resistant

REQUIRED CONSUMABLES / CHEMICALS FOR FIRST OPERATIONS







88500-0005		Starter-kit for 500 analyses CS 580A (500 crucibles, 50 g glass wool, 100 g Combsolid)
90200		Anhydron (magnesium perchlorate), 454 g 1)
90210		Sodium hydroxide, 500 g 1)

FURTHER OPTIONS AND CONSUMABLES

ACCESSORIES (HARDWARE)

88200-3800		TIC-Module
72070		Oxygen regulator
88400-0610		Barcode scanner
88600-0015		Crucible holder

CHEMICALS (FILLINGS FOR GLASS AND QUARTZ TUBES)

90200		Anhydron (magnesium perchlorate), 454 g 1)
90210		Sodium hydroxide, 500 g 1)
90331		Glass wool, 454 g
90332		Glass wool, 50 g
92610		Tube of high vacuum grease, 35 g
88600-0008		Combsolid, 100 g
91000-1005		Copper, flakes, 25 g
90840		Quartz sand, 100 g

88400-0508



Steel wool

CRUCIBLES

90149



Ceramic crucibles, premium, Ø 1",
foil-wrapped, 1,000 pieces

90148



Ceramic crucibles, premium, Ø 1",
bagged, 1,000 pieces

88400-0176

Ceramic filtering crucibles, 100 pieces

88400-0142

Filtering crucibles, 100 pieces, small version

REAGENT TUBES

09090



Reagent tubes 32 x 280 mm, 1 piece

09092



Reagent tube XL size, 54 x 36 x 280 mm

09093



Reagent tube XXL size, length 280 mm

TOOLS FOR OPERATION: SPATULAS, TWEEZERS, TONGS AND OTHER

88400-0229



Tweezers (160 mm), curved, 1 piece

88400-0472



Tweezers (145 mm), straight, 1 piece

88400-0475



Set with 6 spatula and 1 tweezers

88400-0477



Weighing boat, 1 piece

for weighing and usage of granulates

90145






Tongs for ceramic crucibles and boats, 220 mm, 1 piece

90146



Steel pot for preheated crucibles and used crucibles

TOOLS FOR MAINTENANCE

35400-8000		Maintenance kit CS-580A
71010		Brush, 16 mm, 1 piece, for cleaning balance from dust
88400-0473		Powder funnel (plastics), 1 piece, for easy filling of chemical tubes
88400-0490		Rubber plug 29 x 35 x 30 mm, 1 piece, for sealing big glass tubes like 09090
88600-0026		Anhydrone filter tube




CALIBRATION MATERIALS

**Calibration materials may show slight variations depending on the current lot.
To see the current certification please visit www.ELTRA.com.**


COAL: CERTIFIED SULFUR CONTENT

92511-3005		Coal, 50 g, < 0.1 % S
92511-3010		Coal, 50 g, 0.1 – 0.5 % S
92511-3020		Coal, 50 g, 0.5 – 1.0 % S
92511-3030		Coal, 50 g, 1.0 – 1.5 % S
92511-3040		Coal, 50 g, 1.5 – 2.0 % S
92511-3050		Coal, 50 g, 2.0 – 3.0 % S
92511-3060		Coal, 50 g, 3.0 – 4.0 % S
92511-3070		Coal, 50 g, 4.0 – 5.0 % S
92511-3080		Coal, 50 g, >5.0 % S

COAL, PREMIUM, C/H/N/S, ASH, VOLATILE CONTENT, CERTIFIED

92550-3010		Coal, premium, 50 g, < 1.0 % S
92550-3020		Coal, premium, 50 g, > 1 % S
92550-3040		Coal, premium, 50 g, 1.0 – 3.0 % S
92550-3060		Coal, premium, 50 g, > 3.0 % S

COKE, PREMIUM, C/H/N/S, ASH, VOLATILE CONTENT, CERTIFIED

92560-3010		Coke, premium, 50 g
------------	---	---------------------

PET COKE, PREMIUM, C/H/N/S, ASH, VOLATILE CONTENT CERTIFIED

92570-3020		Pet coke, premium, 50 g, > 1 % S
92570-3040		Pet coke, premium, 50 g, > 1 % S

OTHER

90812-3001		Limestone, 25 g, 0.04 % S
90812-3002		Limestone, 25 g, 0.4 % S
90812-3003		Limestone, 25 g, < 5 % C
90812-3004		Limestone, 25 g, 5 – 10 % C
90817-3001		Soil, 25 g, > 2 % C, S
90817-3002		Soil, 25 g, < 1 % C, S
90817-3003		Soil, 25 g, > 2 % C, S
90817-3004		Soil, 25 g, > 2 % C, S
91900-1001		Ore, 30 g, ~1.4 % S
91900-1002		Ore, 30 g, ~4.2 % S
91900-1003		Ore, 30 g, ~3 % S

PRIMARY SUBSTANCES FOR CALIBRATION

90710-3010



EDTA, 50 g

90710-3030

Sucrose, 50 g

90810



Calcium carbonate, 100 g

90821



Barium sulphate, 50 g

90824



Sulfanilic acid, 50 g

91900-2001

Zinc sulfide, 50 g, 32 % S

LIQUID CALIBRATION MATERIAL

Please note: Every analyzer requires PC, monitor, balance and some consumables (crucibles, chemicals) which have to be ordered separately